

# SOILS INTERPRETATION HELP SHEET (Revised 2018)

<p><b>Figure 10.6 - Determining available water capacity (AWC)</b> Field Procedure for Estimating Available Water Capacity</p> <ol style="list-style-type: none"> <li>1. Identify the horizons present in the soil profile.</li> <li>2. Measure the thickness of each horizon.</li> <li>3. Determine the effective depth of rooting.</li> <li>4. For each horizon:             <ol style="list-style-type: none"> <li>a. Determine the texture and the rock fragment (2 mm-25cm) content.</li> <li>b. Find the percent fine earth by subtracting: 100% - percentage rock fragment content = percent fine earth.</li> <li>c. Use the AWC rate that corresponds to the texture of each horizon.</li> <li>d. Multiply the AWC rate by thickness of horizon by percent fine earth to determine the AWC.</li> </ol> </li> <li>5. Total the AWC for all horizons within the effective rooting depth up to 60 inches.</li> <li>6. Determine the correct AWC class.</li> </ol> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="text-align: center;">Soil Texture</th> <th style="text-align: center;">AWC Rate in Inches of Water/Inch of Soil</th> <th style="text-align: center;">AWC Class (Calculated AWC up to 60in)</th> </tr> </thead> <tbody> <tr> <td>Sand, loamy sand</td> <td style="text-align: center;">.06</td> <td style="text-align: center;">Very low -- &lt; 3 in.</td> </tr> <tr> <td>Sandy loam</td> <td style="text-align: center;">.12</td> <td style="text-align: center;">Low -- 3 – 5.99 in.</td> </tr> <tr> <td>Loam, silt loam</td> <td style="text-align: center;">.22</td> <td style="text-align: center;">Moderate -- 6 – 8.99 in.</td> </tr> <tr> <td>Silty clay loam, clay loam</td> <td style="text-align: center;">.17</td> <td style="text-align: center;">High -- 9. - 12 in.</td> </tr> <tr> <td>Silty clay, sandy clay</td> <td style="text-align: center;">.12</td> <td style="text-align: center;">Very high -- &gt;12 in.</td> </tr> <tr> <td>Sandy clay loam</td> <td style="text-align: center;">.15</td> <td></td> </tr> <tr> <td>Clay</td> <td style="text-align: center;">.09</td> <td></td> </tr> </tbody> </table>	Soil Texture	AWC Rate in Inches of Water/Inch of Soil	AWC Class (Calculated AWC up to 60in)	Sand, loamy sand	.06	Very low -- < 3 in.	Sandy loam	.12	Low -- 3 – 5.99 in.	Loam, silt loam	.22	Moderate -- 6 – 8.99 in.	Silty clay loam, clay loam	.17	High -- 9. - 12 in.	Silty clay, sandy clay	.12	Very high -- >12 in.	Sandy clay loam	.15		Clay	.09		<p><b>Table 10.5 - Guide for Internal Drainage and Depth to WT</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Drainage Class</th> <th style="text-align: left;">Mottles</th> </tr> </thead> <tbody> <tr> <td>Excessive (E)/Somewhat excessive (SE) <i>"These soils commonly are loamy sand, sandy loam, or extremely gravelly or cobbly."</i></td> <td>No gray colors or mottles within 72 in.</td> </tr> <tr> <td>Well (W)</td> <td>Gray mottles below a depth of 42 in.</td> </tr> <tr> <td>Moderately well (MW)</td> <td>Gray mottles at depths of 24-41.99 in.</td> </tr> <tr> <td>Somewhat poorly (SP)</td> <td>Gray mottles below the A horizon at depths of 12-23.99 in.</td> </tr> <tr> <td>Poorly (P)</td> <td>Gray mottles in and below the A horizon or at a depth of less than 12 in.</td> </tr> <tr> <td>Very poorly (VP)</td> <td>Gleyed colors or gray mottles to the surface, depressional areas, and evidence of long periods of ponding above the surface.</td> </tr> </tbody> </table>	Drainage Class	Mottles	Excessive (E)/Somewhat excessive (SE) <i>"These soils commonly are loamy sand, sandy loam, or extremely gravelly or cobbly."</i>	No gray colors or mottles within 72 in.	Well (W)	Gray mottles below a depth of 42 in.	Moderately well (MW)	Gray mottles at depths of 24-41.99 in.	Somewhat poorly (SP)	Gray mottles below the A horizon at depths of 12-23.99 in.	Poorly (P)	Gray mottles in and below the A horizon or at a depth of less than 12 in.	Very poorly (VP)	Gleyed colors or gray mottles to the surface, depressional areas, and evidence of long periods of ponding above the surface.
Soil Texture	AWC Rate in Inches of Water/Inch of Soil	AWC Class (Calculated AWC up to 60in)																																					
Sand, loamy sand	.06	Very low -- < 3 in.																																					
Sandy loam	.12	Low -- 3 – 5.99 in.																																					
Loam, silt loam	.22	Moderate -- 6 – 8.99 in.																																					
Silty clay loam, clay loam	.17	High -- 9. - 12 in.																																					
Silty clay, sandy clay	.12	Very high -- >12 in.																																					
Sandy clay loam	.15																																						
Clay	.09																																						
Drainage Class	Mottles																																						
Excessive (E)/Somewhat excessive (SE) <i>"These soils commonly are loamy sand, sandy loam, or extremely gravelly or cobbly."</i>	No gray colors or mottles within 72 in.																																						
Well (W)	Gray mottles below a depth of 42 in.																																						
Moderately well (MW)	Gray mottles at depths of 24-41.99 in.																																						
Somewhat poorly (SP)	Gray mottles below the A horizon at depths of 12-23.99 in.																																						
Poorly (P)	Gray mottles in and below the A horizon or at a depth of less than 12 in.																																						
Very poorly (VP)	Gleyed colors or gray mottles to the surface, depressional areas, and evidence of long periods of ponding above the surface.																																						
<p><b>Table 10.4 - Guide for Determining Soil Permeability</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Texture</th> <th style="text-align: center;">Permeability (inches of water/hour)</th> </tr> </thead> <tbody> <tr> <td>Sand, loamy sand Sandy loam Loam, silt loam</td> <td>Rapid and very rapid (&gt;6.0 in/hr) Moderately rapid (2 - 6 in/hr) Moderate (0.6 – 1.99 in/hr)</td> </tr> <tr> <td>**** Sandy clay loam **** Clay loam, silty clay loam **** Sandy clay **** Silty clay, clay</td> <td>Moderately slow (0.2 - 0.59 in/hr) Moderately slow (0.2 - 0.59 in/hr) Moderately slow (0.2 - 0.59 in/hr) Very slow and slow (&lt; 0.2 in/hr)</td> </tr> <tr> <td><b>NOTE:</b> If the horizon is a fragipan, use the guide below. All fragipans will be "very slow" in permeability.</td> <td>Very slow (&lt; 0.06 in/hr)</td> </tr> <tr> <td>****<b>NOTE:</b> For areas where Kaolinite clays are found, permeability rating used should be moderate.</td> <td>Moderate (0.6 – 1.99 in/hr)  For subsoil permeability, use permeability of most limiting layer (between the base of the surface layer to a depth of 60 inches excluding the CR and R horizons).</td> </tr> </tbody> </table>	Texture	Permeability (inches of water/hour)	Sand, loamy sand Sandy loam Loam, silt loam	Rapid and very rapid (>6.0 in/hr) Moderately rapid (2 - 6 in/hr) Moderate (0.6 – 1.99 in/hr)	**** Sandy clay loam **** Clay loam, silty clay loam **** Sandy clay **** Silty clay, clay	Moderately slow (0.2 - 0.59 in/hr) Moderately slow (0.2 - 0.59 in/hr) Moderately slow (0.2 - 0.59 in/hr) Very slow and slow (< 0.2 in/hr)	<b>NOTE:</b> If the horizon is a fragipan, use the guide below. All fragipans will be "very slow" in permeability.	Very slow (< 0.06 in/hr)	**** <b>NOTE:</b> For areas where Kaolinite clays are found, permeability rating used should be moderate.	Moderate (0.6 – 1.99 in/hr)  For subsoil permeability, use permeability of most limiting layer (between the base of the surface layer to a depth of 60 inches excluding the CR and R horizons).	<p><b>Table 13.2 - Guide for Determining the Shrink-Swell Potential</b> Use thickest layer (10 to 60 inches) Dominant % of Material</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Soil Texture</th> <th style="text-align: center;">Percent Clay</th> <th style="text-align: center;">Shrink-Swell Rating</th> </tr> </thead> <tbody> <tr> <td>Sand, loamy sand, sandy loam, loam, silt loam</td> <td style="text-align: center;">0 - 26.99%</td> <td style="text-align: center;">Low</td> </tr> <tr> <td>** Silty clay loam, clay loam, sandy clay loam</td> <td style="text-align: center;">27 - 39.99%</td> <td style="text-align: center;">Moderate</td> </tr> <tr> <td>*** Silty clay, clay, sandy clay</td> <td style="text-align: center;">&gt; 40%</td> <td style="text-align: center;">High</td> </tr> </tbody> </table> <p>** Kaolinite/Silty clay loam, clay loam, sandy clay loam use Low Shrink-Swell Rating *** Kaolinite/Silty clay, clay, sandy clay use Moderate Shrink-Swell Rating</p>	Soil Texture	Percent Clay	Shrink-Swell Rating	Sand, loamy sand, sandy loam, loam, silt loam	0 - 26.99%	Low	** Silty clay loam, clay loam, sandy clay loam	27 - 39.99%	Moderate	*** Silty clay, clay, sandy clay	> 40%	High																
Texture	Permeability (inches of water/hour)																																						
Sand, loamy sand Sandy loam Loam, silt loam	Rapid and very rapid (>6.0 in/hr) Moderately rapid (2 - 6 in/hr) Moderate (0.6 – 1.99 in/hr)																																						
**** Sandy clay loam **** Clay loam, silty clay loam **** Sandy clay **** Silty clay, clay	Moderately slow (0.2 - 0.59 in/hr) Moderately slow (0.2 - 0.59 in/hr) Moderately slow (0.2 - 0.59 in/hr) Very slow and slow (< 0.2 in/hr)																																						
<b>NOTE:</b> If the horizon is a fragipan, use the guide below. All fragipans will be "very slow" in permeability.	Very slow (< 0.06 in/hr)																																						
**** <b>NOTE:</b> For areas where Kaolinite clays are found, permeability rating used should be moderate.	Moderate (0.6 – 1.99 in/hr)  For subsoil permeability, use permeability of most limiting layer (between the base of the surface layer to a depth of 60 inches excluding the CR and R horizons).																																						
Soil Texture	Percent Clay	Shrink-Swell Rating																																					
Sand, loamy sand, sandy loam, loam, silt loam	0 - 26.99%	Low																																					
** Silty clay loam, clay loam, sandy clay loam	27 - 39.99%	Moderate																																					
*** Silty clay, clay, sandy clay	> 40%	High																																					
	<p><b>*Table 10.3 - Permeability Class</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Permeability Class</th> <th style="text-align: left;">Water Flow in saturated soil (in/hr)</th> </tr> </thead> <tbody> <tr> <td>Very rapid</td> <td style="text-align: center;">&gt; 20.0</td> </tr> <tr> <td>Rapid</td> <td style="text-align: center;">6 - 20.0</td> </tr> <tr> <td>Moderately rapid</td> <td style="text-align: center;">2 – 5.99</td> </tr> <tr> <td>Moderate</td> <td style="text-align: center;">0.6 – 1.99</td> </tr> <tr> <td>Moderately slow</td> <td style="text-align: center;">0.2 - 0.59</td> </tr> <tr> <td>Slow</td> <td style="text-align: center;">0.06 - 0.19</td> </tr> <tr> <td>Very slow</td> <td style="text-align: center;">.01 - .059</td> </tr> <tr> <td>Extremely slow</td> <td style="text-align: center;">&lt;0.01</td> </tr> </tbody> </table>	Permeability Class	Water Flow in saturated soil (in/hr)	Very rapid	> 20.0	Rapid	6 - 20.0	Moderately rapid	2 – 5.99	Moderate	0.6 – 1.99	Moderately slow	0.2 - 0.59	Slow	0.06 - 0.19	Very slow	.01 - .059	Extremely slow	<0.01																				
Permeability Class	Water Flow in saturated soil (in/hr)																																						
Very rapid	> 20.0																																						
Rapid	6 - 20.0																																						
Moderately rapid	2 – 5.99																																						
Moderate	0.6 – 1.99																																						
Moderately slow	0.2 - 0.59																																						
Slow	0.06 - 0.19																																						
Very slow	.01 - .059																																						
Extremely slow	<0.01																																						

Figures and Tables have been condensed and may not match the IML curriculum guide and student handbook. **Figure 12.1 - Guide for determining artificial surface drainage**

Drainage is needed for:

1. Soils that are somewhat poorly drained, poorly drained or very poorly drained, and are nearly level with depressional spots.
2. Sloping soils below seepy areas.

**Table 12.1 Irrigation Guidelines**

Soil Characteristic	Asset	Liability
Surface Soil Texture	Loam, silt loam, silty clay loam, clay loam	All Other Textures
Slope	0 - 3%	> 3%
AWC	> 6 in	0 - 6 in
Depth to High WT	> 2 ft	0 - 2 ft
Permeability	> 0.2 in/hr	< 0.2 in/hr
Rock Fragments >3 in (surface layer)	< 15%	> 15%
Depth of soft or hard bedrock	> 40 in	0 - 40 in

**Table 12.2 - Guide for Determining Hazards or limitations for Cropping**

Possible Hazard or limitation	Soil Characteristics That Indicate A Hazard or Limitation Exists
Slope or Erosion	1. All land slopes longer than 90 ft in excess of 2% slope. 2. Any eroded area where the upper 6-7 inches is either mixed topsoil and subsoil, mostly subsoil, or has gullies.
Available Water Capacity	Less than 10 in of available water in the upper 60 in of the profile.
Surface Drainage	High water table <2 ft and nearly level with depressional spots. Also, sloping areas below seep spots.
Internal Drainage	High water table <3.5 ft.
Rock Fragments (volume upper 10 in)	>15%
Stoniness (surface)	Stones <100 ft apart
Rockiness	10 sq. ft. of rock outcrop per 10,000 sq. ft. of area

**SOILS INTERPRETATION HELP SHEET**  
Revised 2018

Figures and Tables have been condensed and may not match the IML curriculum guide and student handbook.

**Table 13.1 - Guide for Rating Limitations for Pond Reservoir Area**  
For subsoil permeability, use permeability of most limiting layer.

Property	Slight	Moderate	Severe
Permeability	<0.6 in/hr	0.61 - 2.0 in/hr	>2.0 in/hr
Depth to hard bedrock	> 60 in	20 - 60 in	< 20 in
Depth to soft bedrock	> 60 in	20 - 60 in	< 20 in
Slope	< 3%	3 - 8%	> 8%

**Table 13.3 - Guide for Rating Limitations for Dwellings with Basements**

Property	Slight	Moderate	Severe
Depth to WT	> 6.0 ft	2.5 - 6.0 ft	< 2.5 ft
Flooding	None	---	Any flooding
Shrink-Swell (thickest layer 10-60 in)	Low	Moderate	High
Slope	< 8%	8 - 15%	> 15%
Rock Fragments (percent >3 in) (avg. percent volume to a depth of 40 in)	< 15%	15 - 35%	> 35%
Hard Bedrock (Must be OK to hold a basement)	> 60 in	40 - 60 in	< 40 in

**Table 13.4 - Guide for Rating Limitations for Septic Tank Absorption Fields**  
Use the rate of permeability of the dominant percentage of material.

Property	Slight	Moderate	Severe
Permeability (24-60 in)	2.01-6.0 in/hr	0.61-2.0 in/hr	<0.6 or >6 in/hr
Depth to WT	> 6 ft	4 - 6 ft	< 4 ft
Depth to Bedrock (Both soft & hard bedrock)	> 60 in	40 - 60 in	< 40 in
Slope	< 8%	8 - 15%	> 15%
Flooding	None	---	Any flooding
Rock Fragments >3 in (avg. percent volume to a depth of 40 in)	< 15%	15 - 35%	> 35%

**Table 13.5 - Guide for Rating Limitations for Sewage Lagoons**  
Use the rate of subsoil permeability of the dominant percentage of material.

Property	Slight	Moderate	Severe
Permeability	< 0.6 in/hr	0.6 - 2.0 in/hr	> 2.0 in/hr
Depth to WT	> 5 ft	3.5 - 5 ft	< 3.5 ft
Depth to Bedrock (Both soft & hard bedrock)	> 60 in	40 - 60 in	< 40 in
Slope	< 2%	2 - 8%	> 8%
Flooding	None	---	Any flooding
Rock Fragments >3 in (avg. % volume to a depth of 40 in)	< 15%	15 - 35%	> 35%